

SCENEMASTER III

Memory Lighting Desks



- Available in 12/24 or 24/48 channel models
- Large memory capacity with over 500 scenes
- 4 pages of scenemasters with automatic page overlay
- Each submaster can record a scene, a chase or a show
- Recordable up and down fade times
- Multiple independent chase speeds
- Record Beat function for synchronizing chase speeds to live music
- Dynamic VGA colour display & Memory card and print-out options

E-mail: info@theatrelight.co.nz
6 Rowe St., Onehunga, Auckland, New Zealand
Tel: 64-9-622 1187, Fax: 64-9-636 5803
Web: www.theatrelight.co.nz

THEATRELIGHT NZ


Memory Lighting Consoles **SCENEMASTER III**

The Theatrelight Scenemaster 3F has been designed to bring the cost of effective micro-processor controlled stage lighting into an affordable range. Versatile and easy to use, it is ideally suited to the lighting of both large and small venues.

Whatever your needs, the Scenemaster 3F is the lighting controller to enhance your performance.

FEATURES

- Available in 12/24 or 24/48 models
- Standard DMX 512 USITT 1990 output
- Large memory capacity with over 500 scenes
- 5 Year memory retention
- 4 pages of scenemasters with automatic page overlay
- Each submaster can record a scene, chase or a show
- Recordable up and down fade times
- Fade times from 0.1 sec to 10 minutes or instant
- Single button show operation
- Multiple independent chase speeds
- Record Beat function for synchronizing chase speeds to live music
- Wide mode doubles channel capacity
- Memory card and print-out option
- Dynamic VGA colour display provides live monitoring of desk and on-screen Help




Specifications

- Construction:** Powder coated corrosion protected steel frame
- Faders:** 60mm stroke linear faders with custom moulded ABS knobs
- Flash Keys:** Long life heavy duty computer keys with ABS caps
- Electronics:** CMOS micro-processor with 5 year lithium backup battery CMOS memory
- Power Supply:** 100~120 or 220~240VAC with 4 pin male XLR power socket via external 4 pin XLR plug 100~120 or 220~240VAC
- Control Output:** DMX-512 USITT (1990) Digital Multiplex System via 5 pin XLR male socket
- Remote Step Control:** Cue Go, Cue Back and Show Reset via 6.25mm stereo jack socket (short to earth)
- External Audio Input:** Non amplified 6.3mm mono jack

Dimensions

Model	Length	Weight
Scenemaster 3 12/24	451mm	6Kg
Scenemaster 3 24/48	679mm	9Kg



Your Local Distributor:

THEATRELIGHT NZ

Theatrelight Ltd, 6 Rowe St. Onehunga, Auckland, New Zealand
 Tel: 64-9-622 1187, Fax: 64-9-636 5803
 Internet: www.theatrelight.co.nz, e-mail: info@theatrelight.co.nz